



# Moto Fork Oil 5W and 10W

## ■ Description

Hydraulic oil especially designed for motorcycle shock absorbers and suspension forks. Excellent performance under high stress and suitable for all types of use, both urban and sports. Available at two levels of viscosity SAE 5W and SAE 10W.

## ■ Properties

- Good performance when faced with changes in temperature due to its high viscosity index.
- Good shock absorbing characteristics and compatibility with oil seals.
- Excellent anti-friction performance thanks to its special additives.
- Great resistance to ageing and good anti-rusting and anticorrosive properties.

## ■ Quality level

- DIN 51524 Part 2

## ■ Technical characteristics

	UNIT	METHOD	5W	10W
SAE Grade			5W	10W
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.875	0.845
Viscosity at 100°C	cSt	ASTM D 445	4.9	8.3
Viscosity at 40°C	cSt	ASTM D 445	22	46
Viscosity at -25°C	cP	ASTM D 5293	<6000	<6000
Viscosity index	-	ASTM D 2270	150	157
Flash point, open cup	°C	ASTM D 92	200	232
Pour point	°C	ASTM D 97	-40	-40

## ■ Available in

---

1 litre plastic containers.

## ■ Hazard identification

---

This product is not classified as toxic or hazardous under current legislation.

## ■ Handling

---

This product must be used taking care to avoid prolonged contact with the skin. It is advised that you wear gloves, visors or goggles to avoid splashes.

## ■ Health and safety hazards

---

**Inhalation:** Given that it is not a particularly volatile product, the risk of inhalation is minimal.

**Ingestion:** Do not induce vomiting. Provide water. Seek medical advice.

**Contact with the skin:** Wash with plenty of water and soap.

**Eyes:** Wash with plenty of water.

**General measures:** Seek medical advice.

## ■ Firefighting measures

---

No special measures required.

**Fire-extinguishing measures:** Foams, dry chemicals, CO<sub>2</sub>, water spray. Do not apply the jet of water directly as this could cause the product to disperse.

## ■ Environmental precautions

---

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

**Decontamination and cleaning:** Treat like an accidental oil spill. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

**Emergency phone number. National Toxicology Institute 91 562 04 20**

A safety information file is available on request.

repsolypf.com  
901 111 999

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.