

# Moto Transmisiones 10W40

## Description

Lubricant oil designed especially for motorcycle gearboxes. Its researched formula provides excellent shear resistance and guarantees the operation of clutches bathed in engine oil.

## Recommended uses

Motorcycle gearboxes where the manufacturer recommends a lubricant with viscosity SAE 10W40.

# Properties

- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Provides optimum friction in clutch discs, preventing slippage.
- Enables speed and clutch changes to be carried out smoothly and precisely.

## Quality level

• JASO T-903:2006 MA2 (Code M034RYL007)

## Technical characteristics

	UNIT	METHOD	VALUE
Density at 15°C	g/cm <sup>3</sup>	ASTM D 4052	0.854
Viscosity at 100°C	cSt	ASTM D 445	15
Viscosity at 40°C	cSt	ASTM D 445	97
Viscosity at -25°C	cP	ASTM D 5293	7000 max
Viscosity index	-	ASTM D 2270	164
Flash point, open cup	°C	ASTM D 92	236
Pour point	٥C	ASTM D 97	-42
T. B. N.	mg KOH/g	ASTM D 2896	6.6
Sulphated ashes	% in weight	ASTM D 874	0.8

# Available in

1 litre plastic containers.

## Hazard identification

This product is not classified as toxic or hazardous under current legislation.

### Handling

This product must be used taking care to avoid prolonged contact with the skin. It is advised that you wear gloves, visors or goggles to avoid splashes.

### Health and safety hazards

**Inhalation:** Given that it is not a particularly volatile product, the risk of inhalation is minimal.

Ingestion: Do not induce vomiting. Provide water. Seek medical advice.Contact with the skin: Wash with plenty of water and soap.Eyes: Wash with plenty of water.General measures: Seek medical advice.

### Firefighting measures

No special measures required.

Fire-extinguishing measures: Foams, dry chemicals,  $CO_2$ , water spray. Do not apply the jet of water directly as this could cause the product to disperse.

## Environmental precautions

Risk of physical contamination when spilled (waterways, coastal areas, soils, etc.) due to its floatability and oily consistency; could cause harm to flora and fauna on contact. Avoid material getting into water outlets.

Decontamination and cleaning: Treat like an accidental oil spill. Prevent dispersion using mechanical barriers and remove by physical or chemical means.

**Emergency phone number. National Toxicology Institute 91 562 04 20** A safety information file is available on request.

repsolypf.com 901 111 999

Unless otherwise indicated, the figures cited in technical characteristics should be considered typical.